Work Write-Up 2022 0314 Williams

Williams, Essie 1070 Maynard Street Macon, Georgia 31217 Home Phone: 478 745 4474

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Contractor shall also carry worker's compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements concerning warranty.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0425 Replace up to 20% of Roof Decking.

Replace up to 20% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ¹/₂" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0315 Banks

Banks, Reginald & Sharon 1097 Lamont Street Macon, Georgia 31204 Cell Phone: 478 318 6632

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Contractor shall also carry worker's compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work, before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work_on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color. (RIGHT and LEFT SIDE Of the Structure)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0475 Replace up to 30% of Roof Decking.

Replace up to 30% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0316 Holloway

Holloway, Alberta 835 Plant Street Macon, Georgia 31201 Home Phone: 478 742 5036

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner and Program Administrator. Refer to the project contract for specific requirements concerning warranty.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work_on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0775 Replace up to 100% of Roof Decking.

Replace up to 100% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1125 Install Metal Flashing on Two (2) Chimneys

Properly install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimney. Aluminum flashing is not permitted.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0317 Whitehead

Whitehead, Randolyn 2574 Medford Place Macon, Georgia 31206 Cell Phone: 478 365 9668

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs, and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color. (Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0425 Replace up to 20% of Roof Decking.

Replace up to 20% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1350 Install Rainwater Diverter at Entrance

Install a non-corrosive metal rainwater diverter above entrance.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0318 Ringwood

Ringwood, Vuneita 3983 Marse Allen Rd Macon, Georgia 31206 Home Phone: 478 788 3134

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color. (Rotten Fascia on All Perimeter)

35.0325 <u>Remove All Roof Covering Material down to Sheathing</u>

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 40% of Roof Decking

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @____%

Work Write-Up 2022 0319 Johnson

Johnson, Mary 4928 Pinefield Drive Macon, Georgia 31206 Cell Phone: 478 978 7405

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color. (Right and Rear)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 40% of Roof Decking.

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @____%

Work Write-Up 2022 0320 Smith

Smith, Moseeva 2776 Houston Avenue Macon, Georgia 31206 Cell Phone: 478 335 9712

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and $\frac{3}{4}$ " thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color.

(Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0600 Replace up to 50% of Roof Decking.

Replace up to 50% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Total Cost

22

Work Write-Up 2022 0321 Williams

Williams, Jacqueline 2990 Hester Rd Macon, Georgia 31217 Cell Phone: 478 233 0136

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to Verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and $\frac{3}{4}$ " thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color.

(Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace Up to 40% of Roof Decking

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1350 Install Rainwater Diverter at Entrance

Install a non-corrosive metal rainwater diverter above entrance.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0322 Morris

Morris, Melba 3950 Bloomfield Drive Macon, Georgia 31206 Cell Phone: 803 640 5809 Cindy Walton (Daughter)

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be of high quality, 2) be installed in accordance with manufacturer's specs and, 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0775 Replace Up to 100% of Roof Decking

Replace up to 100% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for Compliance Inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1125 Install Metal Flashing on Chimneys

Properly install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimney. Aluminum flashing is not permitted.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0323 Johnson

Johnson, Curtis 5541 Jeffersonville Rd Dry Branch, Georgia 31020 Cell Phone: 478 213 3126

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0250 Repair the Cornice at Roof Overhangs

Replace severely defective rotten and missing cornice components including fascia boards, soffit boards, frieze boards and rafter tails. New material to match remaining material as closely as possible.

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0600 Replace up to 50% of Roof Decking.

Replace up to 50% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @____%

Work Write-Up 2022 0324 Poole

Poole, Deborah 2280 Robin Hood Road Macon, Georgia 31206 Cell Phone: 478 714 5621

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Contractor shall also carry worker's compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements concerning warranty.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0475 Replace up to 30% of Roof Decking.

Replace up to 30% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1350 Install Rainwater Diverter at Entrance

Install a non-corrosive metal rainwater diverter above entrance.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0325 Jones

Jones, Thelma 3267 Masseyville Rd Macon, Georgia 31217 Cell Phone: 478 258 4120

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Contractor shall also carry worker's compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work, before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work_on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color.

(Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 40% of Roof Decking.

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1350 Install Rainwater Diverter at Entrance

Install a non-corrosive metal rainwater diverter above entrance.

COST SUMMARY	Material – Labor	
	Overhead and Profit @%	
	Total Cost	

Work Write-Up 2022 0326 Jones

Jones, Cora 823 Perry Drive Macon, Georgia 31217 Cell Phone: 478 284 2381

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner and Program Administrator. Refer to the project contract for specific requirements concerning warranty.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work_on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0775 Replace up to 100% of Roof Decking.

Replace up to 100% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ¹/₂" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0327 Gardner

Gardner, Jeanette & Lawrence 4165 San Carlos Drive Macon, Georgia 31206 Cell Phone: 478 338 5777

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs, and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color. (Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0600 Replace up to 50% of Roof Decking.

Replace up to 50% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @ %

Work Write-Up 2022 0328 Rambeau

Rambeau, Peggy 4112 W Hickory Court Macon, Georgia 31210 Cell Phone: 478 757 1299

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01.0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01.0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 40% of Roof Decking

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0329 Gilmore

Gilmore, Betty 1955 Canterbury Rd Macon, Georgia 31206 Cell Phone: 478 250 5625

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0425 Replace up to 20% of Roof Decking.

Replace up to 20% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @____%

Work Write-Up 2022 0330 Brown

Brown, Georgia 1172 East Cordele Avenue Macon, Georgia 31217 Cell Phone: 478 731 6989

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 30% of Roof Decking.

Replace up to 30% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

35.1350 Install Rainwater Diverter at Entrance

Install a non-corrosive metal rainwater diverter above entrance.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0331 Battle & Allen

Battle, Dale & Allen, Andrew 5821 East Ocmulgee Blvd Macon, Georgia 31217 Cell Phone: 478 621 3758

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to Verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0775 Replace Up to 100% of Roof Decking

Replace up to 10% of any rotten, badly warped, or broken roof decking and fasteners. Materials shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @____%

Work Write-Up 2022 0332 Watson

Watson, Deborah 908 Quinlan Drive Macon, Georgia 31206 Cell Phone: 478 508 7399

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be of high quality, 2) be installed in accordance with manufacturer's specs and, 3) meet requirements of code inspections.

01.0225 <u>General Warranty</u>

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0225 Install Fascia Board Over End of Rafter Tails

Install new 2" X 4" Pine sub-fascia and ¾" thick # 2 spruce fascia board to cover the ends of the rafter tails. Replace severely defective, rotten, and missing rafter tails. Prep and paint to match existing color.

(Rotten Fascia on All Perimeter)

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace Up to 40% of Roof Decking

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for Compliance Inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least ½" into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%

Work Write-Up 2022 0333 Albritton

Albritton, Rose 3500 Doster Way Macon, Georgia 31217 Cell Phone: 478 461 1166

Tuesday, April 12, 2022 Location Prepared By: Antonio Simmons

GENERAL REQUIREMENTS

01.0025 Permits and Licenses

Contractor shall obtain, pay for and post on site all permits and licenses necessary to complete this project. Contractor and subcontractors must have current licenses required by the State, County and City.

01. 0050 Code Compliance

All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet with the approval of local code enforcement officials.

01. 0075 Insurance Requirements

The Contractor shall maintain such insurance as will protect him from claims for damages for personal injury, including death, which may arise from work performed on this project, whether such work be by himself or by any subcontractor or any one directly or indirectly employed by either of them. Contractor shall present Program Administrator with certificate of insurance evidencing comprehensive public liability insurance coverage not less than \$100,000/\$300,000 in the event of bodily injury including death and \$50,000/\$100,000 in the event of property damage arising out of the work performed by the Contractor. Worker's Compensation insurance if required by State law, Program Administrator or Homeowner.

01.0150 Contractor to verify Measurements, Sizes and Quantities

All measurements, sizes and quantities in this Work Write-Up are APPROXIMATE. The Contractor is responsible for verifying exact measurements, sizes, and quantities prior to submitting a quote.

01.0200 Workmanship and Material Standards

Contractor to perform work specified in Work Write-Up in a high-quality good workman-like manner using specified materials or approved equals. Materials must: 1) be high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code inspections.

01.0225 General Warranty

Materials installed and work performed shall have a one-year Contractor warranty from the date of final acceptance of the work by the Homeowner & Program Administrator. Refer to project contract for specific requirements.

01.0250 Scheduling Work

Contractor to schedule work between 8:00am and 6:00pm, Monday through Friday. Requests to work before these hours and on weekends must be approved by the Homeowner and Program Administrator.

01.0275 Compliance Inspections

Contractor to call Program Administrator for inspection of all work that will be concealed from view following completion of work on that Item. Check each spec to see if a compliance inspection is required. Work concealed without an inspection may cause payment delays and denials.

01.0325 Protect House Contents from Damage during Work

Contractor shall take steps to protect house and contents from damage during project.

01.0350 Repair Damage Caused to Property during Work

Contractor is responsible for professionally repairing or replacing building and site components damaged because of construction activity.

01.0375 Prime Bare Wood

The exposed face of all newly installed wood and all wood scraped down to bare wood must be primed with appropriate primer.

01.0475 Reduce Airborne Dust during Construction

Contractor to take steps necessary to reduce and contain airborne dust created during construction, demolition, and removal of defective paint. Wet scrape if removing defective paint. Do Not use electric sanders or torches to remove paint. Contractor and workers are encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.

01.0500 GENERAL CLEANUP

35.0325 Remove All Roof Covering Material down to Sheathing.

Remove all roof covering material down to roof sheathing or furring strips. Remove all debris to legal dump site. Take precautions to protect plants, shrubs, trees, and fences from damage during removal.

35.0525 Replace up to 40% of Roof Decking.

Replace up to 40% of any rotten, badly warped, or broken roof decking and fasteners. Material shall match remaining material as closely as possible. Call Program Administrator for compliance inspection.

35.0925 Install New Shingles on Roof Decking

Install 15 lb. asphalt saturated felt and new 220 lb. or heavier Class A three-tab fiberglass self-sealing strip shingles on top of roof decking using 8 nails per shingle. Install starter course at edges of roof. Shingles to have a 20-year limited manufacturer's warranty. Install an aluminum drip edge with a white baked on enamel finish at all fascia boards and barge rafters. Install metal flashing tucked behind siding at intersections of roof and walls. Install galvanized metal flashing tucked securely and at least $\frac{1}{2}$ " into masonry units of chimneys. Program Administrator will select color. Replace all vent pipe and electrical service head flashing.

35.1075 Install Ridge Vent

Install continuous metal ridge vent along ridge lines of roof. Stop vents 18" from end of ridge line or from intersections of ridge lines. Make sure decking at ridge line is cut back at least 1" from edge of ridge pole so that the attic can ventilate.

COST SUMMARY

Material – Labor

Overhead and Profit @_____%